



# ROGUE

**PUMP COMPANY®**  
A LIMITED LIABILITY COMPANY

## MAX RGT-15/ SPECIFICATIONS

### Pump Specifications

Flow-rate  
 Liquid/Medium  
 Suction Pressure  
 Gas Dissolution (air)  
 Discharge Pressure  
 Shaft Seal Type  
 Pump Mounting  
 Impeller(s)  
 Fitting Dimensions  
 Inlet  
 Outlet  
 Gas Inlet  
 Weight  
 Pump  
 Pump & Motor

### English/Metric

**15 gpm/57 lpm (approx\*)**  
**Liquid/gas**  
**Flooded**  
**12 cfh, 10% maximum**  
**184ft/56m (80psi)**  
**Mechanical seal**  
**Close coupled**  
**Single stage**  
  
**1"/DN 25, flanged**  
**1"/DN 25, flanged**  
**1/4" NPT/DN 6**  
  
**35 lbs/15.9 kg**  
**74 lbs/33.5 kg**

### Materials of Construction

Body  
 Shaft Button  
 Impeller  
 O-ring(s)  
 Seal  
 Finish

**Ductile iron**  
**304 stainless steel**  
**Carbon steel**  
**Viton**  
**Ceramic/C, 304 SS, Viton**  
**Metallic blue top-coat**  
**Rust inhibited pre-coat**

### Motor

Horsepower  
 Efficiency  
 Speed  
 Material  
 Enclosure Type  
 Service Factor  
 Frame  
 FLA

**3 hp**  
**Premium, 86.5%**  
**3450 rpm**  
**Carbon steel, painted**  
**TEFC**  
**1.15**  
**145JM**  
**7.9-7.2/3.6**

### Utilities Required

Phase/Hz/Voltage

**3/60/208:230-460v**

\* Flow rate determined by fluid/gas, temperature and operating parameters.




# ROGUE

**PUMP COMPANY®**  
A LIMITED LIABILITY COMPANY

## MAX RGT-15 PUMP CURVE


### ENGLISH UNITS



Fluid specific gravity 1.0 @ 70°F

3hp 230v-460v 3p 60Hz 3450rpm

### METRIC UNITS



Fluid specific gravity 1.0 @ 21°C

3hp 230v-460v 3p 60Hz 3450rpm