


All bolt holes are 7/16".

<b>Model: MAX RGT-30 S</b>	
Flow Rate	30 gpm
Air Flow Rate	24 cfh
Seal	Mechanical
Shaft Diameter	7/8"
Weight	95 lbs
<b>Fittings</b>	
Inlet	1 1/4" Flange
Outlet	1" Flange
Air Inlet	1/4"
<b>Materials</b>	
Shaft Button	316 SS
Impeller	316 SS
O-Ring	Viton
Mechanical Seal	Viton
Body	304 SS
<b>Motor</b>	
Speed	3450 rpm
Horsepower	5 hp
Efficiency @ 100% Load	Premium, 88.5%

REV	REVERSION DESCRIPTION	DATE	SIGNATURE

CUSTOMER: <b>Sales Model</b>		 Rogue Pump Company, LLC 19215 SE 34th Street Suite 106-202 CAMAS, WA 98607	
<small>THE INFORMATION HEREIN IS PROPRIETARY TO ROGUE PUMP COMPANY, LLC. NO PORTION OF IT SHALL BE COPIED, DISCLOSED OR USED FOR DESIGN OR MANUFACTURE EXCEPT WITH SPECIFIC WRITTEN CONSENT FROM ROGUE PUMP COMPANY</small>		TITLE: <b>MAX RGT-30 S</b>	
DRAWN BY: <b>REW</b>	DRAWING NO. <b>R-30-S001</b>	DRAWING SIZE <b>B</b>	REV
CERTIFIED:	DATE: <b>12/17/15</b>	SCALE: <b>1:4</b>	SHEET: <b>1 of 1</b>

**CONFIDENTIAL**